



Mobil Super 2000

Premium Semi-Synthetic Passenger Vehicle Engine Oil

Product Description

The Mobil Super 2000 range of lubricants are enhanced-premium semi-synthetic engine oils, designed to provide an excellent level of protection and performance.

Features and Benefits

Mobil Super 2000 products are industry proven so you can trust you will get the performance you want from your vehicle. Mobil Super 2000 5W-20 and 5W-30 contain low friction semi-synthetic formulation which increases engine efficiency and offers greater fuel economy.

Mobil Super 2000 provides:

- Excellent wear protection
- Excellent engine cleanliness
- Excellent high temperature protection
- Excellent fuel economy (for SAE 5W-20 and 5W-30)

Applications

Mobil Super 2000 products are formulated to give you confidence of protection beyond that of conventional oils. We particularly recommend it for the following vehicle types and conditions:

- Latest engine technologies
- Gasoline and Diesel
- Passenger cars, SUV's, light trucks and vans
- Highway cruising
- Normal to occasionally severe operating conditions
- Turbo-Chargers
- High Performance Engines
- Stop and Go City Driving

Always consult your owner's manual to check recommended viscosity grade and specifications for your particular vehicle.

Specifications and Approvals

Mobil Super 2000 meets or exceeds the requirements of:	5W-20	5W-30	5W-40
API SN	X	X	X
API SM	X	X	X
ILSAC GF-5	X	X	

Mobil Super 2000 is also recommended by ExxonMobil for use in applications requiring:	5W-20	5W-30	5W-40
API CF	X	X	X
ILSAC GF-4	✓	✓	

Typical Properties

Mobil Super 2000

SAE Grade	5W-20	5W-30	5W-40
Viscosity, ASTM D 445			
cSt @ 40° C	48	62	85
cSt @ 100° C	8.5	10.5	14.0
Viscosity Index, ASTM D 2270	155	160	170
Sulfated Ash, wt%, ASTM D 874	0.8	0.8	0.8
HTHS Viscosity, mPa·s @ 150° C, ASTM D4683	2.6	3.1	3.7
Pour Point, °C, ASTM D 97	-30	-33	-33
Flash Point, °C, ASTM D 92	220	220	220
Density @15° C kg/l, ASTM D 4052	0.85	0.86	0.86

Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the Internet, or will be provided by seller to customers if and as legally required. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment

The Mobil logotype, the Pegasus design, and Mobil Super are trademarks of Exxon Mobil Corporation, or one of its subsidiaries.

8-2015

ExxonMobil Asia Pacific Pte Ltd
 Jakarta Representative Office
 Wisma GKBI 27th Floor
 Jl. Jenderal Sudirman No. 28
 Jakarta 10210
 Indonesia

+62 21 574 0707

<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit www.exxonmobil.com

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

Copyright © 2001-2016 Exxon Mobil Corporation. All rights reserved.